

**Product: Orontas SMOOTH**

Date created: 01/01/2010  
Date revised: 06/14/2010

---

## 1. Identification of Substance/Preparation and of the Company

---

<b>Product name:</b>	SMOOTH	<b>Supplier:</b>	Orontas Inc.
<b>Product use:</b>	Lubricant		135 Queens Plate Dr.
<b>Issued By:</b>	Orontas Inc.		Suite 600
			Toronto, ON
			M9W 6V7 Canada
			Phone: 416 792 1076
<b>Emergency Telephone:</b>	CANUTEC (613) 996-6666	<b>Manufacturer:</b>	Orontas Inc.

---

## 2. Hazard Identification

---

Not expected to be a health, safety or environmental hazard. Product is conductive; keep away from electrical systems.

<b>Inhalation</b>	Negligible, unless heated to produce vapors. Vapors or finely misted materials may irritate the mucous membranes and cause irritation, dizziness, and nausea. Remove to fresh air.
<b>Eyes</b>	May cause irritation. Irrigate eye with water for at least 15 to 20 minutes. Seek medical attention if symptoms persist.
<b>Skin Contact</b>	Prolonged or repeated contact is not likely to cause significant skin irritation. Material is sometimes encountered at elevated temperatures. Thermal burns are possible.
<b>Ingestion</b>	No hazards anticipated from ingestion incidental to industrial exposure.

---

## 3. Composition / Information on Ingredients

---

This product contains no hazardous materials.

---

## 4. First-Aid Measures

---

<b>Inhalation</b>	Remove from area of exposure; seek medical attention if symptoms persist.
<b>Eyes</b>	Irrigate eyes with a heavy stream of water for at least 15 to 20 minutes.
<b>Skin Contact</b>	Wash exposed areas of the body with soap and water.
<b>Ingestion</b>	Give one or two glasses of water to drink. If gastro-intestinal symptoms develop, consult medical personnel. (Never give anything by mouth to an unconscious person.)

---

## 5. Fire Fighting Measures

---

<b>Flash Point</b>	130.0°C min (Method Used: ASTM 93)
<b>Flammability Limits</b>	None Known
<b>Extinguishing media</b>	Dry chemical, foam, halon, CO2, water spray (fog). Water stream may splash the burning liquid and spread fire.
<b>Special fire fighting procedures</b>	Use water spray to cool drums exposed to fire.
<b>Protective measures in fire</b>	Oil soaked rags can cause spontaneous combustion if not handled properly. Before disposal, wash rags with soap and water and dry in well ventilated area. Firefighters should use a self-contained breathing apparatus to avoid exposure to smoke and vapor.

**Product: Orontas SMOOTH**

Date created: 01/01/2010  
Date revised: 06/14/2010

---

## 6. Accidental Release Measures

---

Remove sources of ignition, contain spill to smallest area possible. Stop leak if possible. Pick up small spills with absorbent materials such as paper towels, Oil Dry, sand or dirt. Recover large spills for salvage or disposal. Wash hard surfaces with safety solvent or detergent to remove remaining oil film. Greasy nature will result in a slippery surface.

---

## 7. Handling and Storage

---

Store in closed containers between 50°F and 120°F. (10°C and 48°C)  
Keep away from oxidizing agents, excessive heat, and ignition sources.  
Store and use in well-ventilated areas.  
Do not store or use near heat, spark, or flame, store out of sun.  
Do not puncture, drag, or slide this container.  
Drum is not a pressure vessel; never use pressure to empty.

---

## 8. Exposure Controls/Personal Protection

---

<b>Repertory Protection</b>	If vapors or mists are generated, wear a NIOSH approved organic vapor/mist respirator.
<b>Protective Clothing</b>	Safety glasses, goggles, or face shield are recommended to protect eyes from mists or splashing. PVC coated gloves are recommended to prevent skin contact.
<b>Other Protective Measures</b>	Employees must practice good personal hygiene, washing exposed areas of skin several times daily and laundering contaminated clothing before re-use.

---

## 9. Physiological and Chemical properties

---

Boiling Point, 760 mm Hg:>200°C Volatiles, % by Volume: <2  
Specific Gravity (H2O=1): 0.88 Solubility in H2O, % by Volume: Insoluble  
Vapor Pressure, mm Hg: <2 Evaporation Rate, Butyl Acetate=1: <1  
Vapor Density, Air=1 >1  
Appearance and Odor: pale yellow liquid, mild odor

---

## 10. Stability and Reactivity

---

<b>General</b>	This product is stable and hazardous polymerization will not occur.
<b>Materials and conditions to avoid</b>	Strong oxidizing agents
<b>Hazardous decomp. products</b>	Combustion produces carbon monoxide, carbon dioxide along with thick smoke.

---

## 11. Toxicological Information

---

<b>Sensitization</b>	No allergic reaction is known.
<b>Genotoxicity</b>	No known heritable or mutagenic effects.
<b>Carcinogenicity</b>	This substance has no evidence of carcinogenic properties.
<b>Reproduction toxicity</b>	No known reproductive effects.
<b>Inhalation</b>	Vapour may irritate respiratory system or lungs.
<b>Ingestion</b>	Nausea, vomiting.
<b>Skin</b>	No specific health warnings noted.
<b>Eyes</b>	May cause temporary eye irritation.
<b>Route of entry</b>	Skin and/or eye contact.

**Product: Orontas SMOOTH**

Date created: 01/01/2010  
Date revised: 06/14/2010

---

## 12. Ecological Information

---

<b>Ecotoxicity</b>	Not classified as dangerous to the environment.
<b>Mobility</b>	The product is insoluble in water and will spread on the water surface.
<b>Bioaccumulative potential</b>	The product is not bioaccumulating.
<b>Persistence and degradability</b>	The chemical is readily biodegradable.

---

## 13. Disposal Considerations

---

Waste may be disposed of by a licensed waste disposal company. Contaminated absorbent material may be disposed of in an approved landfill. Follow local, state and federal disposal regulations.

---

## 14. Transportation Information

---

**UN HAZARD CLASS:** N/A

**NMFC (National Motor Freight Classification):**

PROPER SHIPPING NAME: Fatty acid ester  
IDENTIFICATION NUMBER: 144920  
SHIPPING CLASSIFICATION: 65

---

## 15. Regulatory Information

---

**OSHA STATUS:**

This product is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, thermal processing and decomposition fumes from this product may be hazardous as noted in Sections 2 and 3.

**TSCA STATUS (Toxic Substance Control Act):**

This product is listed on TSCA.

**CERCLA (Comprehensive Response Compensation and Liability Act):**

NOT reportable.

**SARA TITLE III (Superfund Amendments and Reauthorization Act):**

Section 312 Extremely Hazardous Substances:  
None

Section 311/312 Hazard Categories:

Non-hazardous under Section 311/312

Section 313 Toxic Chemicals:

None

**RCRA STATUS (Resource Conservation and Recovery Act):**

If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste, (40 CFR 261.20-24)

**CALIFORNIA PROPOSITION 65:**

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986. This product contains no chemicals known to the State of California to cause cancer.

**Product: Orontas SMOOTH**

Date created: 01/01/2010  
Date revised: 06/14/2010

---

## 16. Other Information

---

This information relates only to the specific material designated, and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, expressed or implied, is made as to its accuracy, reliability or completeness, and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of its use. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.